

Intelligent Integration of a Vibration Sensor Allowing Synchronization to Application.



Pulsarlube Mi

## Intelligent Machine Synchronized Automatic Lubricator

### Features & Advantages

<b>Vibration Sensor</b>	Lubricator operates only when vibration is detected on the installed application
<b>Cost Savings</b>	Substantial savings from the use of replaceable grease pouches and battery packs (Service Pack)
Easy Installation	Place the magnetic vibration sensor on any flat metal surface
More Peliable &	A project amount of groups in delivered only when the equipment is in energian, avoiding the

# More Reliable & Precise Lubrication

A pre-set amount of grease is delivered only when the equipment is in operation, avoiding the possibility of over lubrication and waste

## Other Features

- Easy to adjust dispensing periods in operation
- Easy to install in hazardous & confined areas
- Transparent container for easy visual inspection of remaining lubricant

## Typical Industries and Applications







- Motors and pumps from municipal water & waste water treatment facilities
- Paper mills, steel mills and cement plants where water & excessive contaminants exist
- Electric motors, pumps, blowers and fans
- Applications where synchronized lubricators cannot be wired to an external power supply or PLC

## Overview





## Product Specifications

#### **Grease Pouch Capacity**

60ml / 125ml / 250ml (capacity setting available)

#### **Power Supply**

DC 4.5V Battery Pack (replaceable) Standard : Alkaline Battery Optional : Lithium Battery

### Operating Pressure

30 ~ 60bar (435 ~ 870psi)

### Operating Temperature

Standard Alkaline Battery :  $-15^{\circ}\text{C} \sim 60^{\circ}\text{C}$  ( $5^{\circ}\text{F} \sim 140^{\circ}\text{F}$ ) Optional Lithium Battery :  $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$  ( $-40^{\circ}\text{F} \sim 140^{\circ}\text{F}$ )

#### **Dispensing Periods**

1 ~ 12 month

#### Single Point Remote Installation

Max. 1m (3.3ft) with Ø6 tube

#### **Multi-Point Installation**

Max. 1m (3.3ft) with Ø6 tube (Up to 2 lube points)

#### **Dispensing Volume Size**

0.34ml/stroke (@20°C/68°F)

#### **Product Certifications & IP Code**

CE

#### **Vibration Detector**

Piezoelectric Cantilever-type Film Sensor Adjustable Sensitivity Range Connection Wire Length : 1.2m

#### Service Life of Battery Pack

60ml / 125ml : Up to 2 years 250ml : Up to 1 year 6 months

#### **Product Dimensions**

183mm (H) x 91mm (Ø) \*Excludes Vibration Sensor

Rev 04

