



# 20 Volt Lithium-Ion Grease Gun

**Built-in Intelligence**



**LCD with real-time  
information:**

- Grease meter
- Grease level gauge
- Battery capacity gauge

**Two flow rates:**

- High — 6 oz/min  
(170 g/min)
- Low — 4 oz/min  
(113 g/min)

**24 grease cartridges per  
battery charge**






### Convenient

- LED flashlight with on/off control



### Patented Airflow Management

- Optimizes motor and transmission life



### Durable & Efficient

- Ball and needle bearings
- Curved slot yoke optimizes mechanical efficiency
- Case-hardened piston for wear and bend resistance
- Impact-resistant LCD lens surrounded by impact-absorbing bezel



### Ergonomic

- Shape, weight and balance designed for less physical strain
- Soft, comfortable grip

**Precise Lubrication – Built-in Intelligence – Only from the Lubrication Specialists**



# Multi-function LCD

## LCD and Icons Keep You in Control

Button resets functions, turns flashlight on or off and toggles between ounces and grams



Switch allows you to choose between two flow rates



Display turns red during stall condition



Display flashes red when the gun loses prime or runs out of grease



Battery level flashes to signify low voltage



Grease level flashes when low grease condition occurs





## Specifications

| Model Number | Li-Ion Battery |         |      | 70-minute Charger | Pressure                | Flow Rate               |                         | Cartridges per Battery Charge |           | Weight             |
|--------------|----------------|---------|------|-------------------|-------------------------|-------------------------|-------------------------|-------------------------------|-----------|--------------------|
|              | Quantity       | Voltage | mAh  |                   |                         | High                    | Low                     | High Speed                    | Low Speed |                    |
| 596-A        | 1              | 20 V*   | 2500 | 110 V/60 Hz       | 10,000 psi<br>(690 bar) | 6 oz/min<br>(170 g/min) | 4 oz/min<br>(113 g/min) | 13                            | 15        | 6.3 lb<br>(2.9 kg) |
| 596-B        | 2              |         |      | 220 V/50 Hz       |                         |                         |                         |                               |           |                    |
| 596-C        | 1              |         |      |                   |                         |                         |                         |                               |           |                    |
| 596-D        | 2              |         |      |                   |                         |                         |                         |                               |           |                    |

\*Maximum initial voltage without workload

## Accessories

| Mobile Charger | Carrying Strap | 20 V Li-Ion Battery | Pressure Relief Valve | Bulk Loader Filling |
|----------------|----------------|---------------------|-----------------------|---------------------|
| 343289         | 339812         | 343291              | 340338                | 322610              |



1057 Red Ventures Drive  
Suite 100  
Fort Mill, SC 29707  
Toll Free U.S.: 866-4-Alemite  
Toll Free Canada: 800-267-8022  
International: 803-802-0001  
Fax U.S.: 800-648-3917  
Fax Canada: 800-267-2880  
Fax International: 803-802-0192  
www.alemite.com  
LIT194 12/18  
Alemite® is a registered trademark of Alemite LLC



4404 Central Parkway  
Hudsonville, MI 49426  
Phone: (616) 538-5700  
Fax: (616) 538-0888  
www.mifp.com



**Precise Lubrication – Built-in Intelligence – Only from the Lubrication Specialists**